



Call Potter-Roemer for current listings and approvals. Dimensions are subject to manufacturers tolerance and change without notice. We assume no responsibility for use of superseded or void data.

# AUTOMATIC FIRE SPRINKLER, HEADS AND ACCESSORIES

## AUTOMATIC FIRE SPRINKLERS

**REGULARLY FURNISHED:** Brass frame with deflector, color coded actuating member, 1/2" male N.P.T. inlet x 1/2" orifice discharge. Type and fusing temperature as selected by Figure Number.

**OPTIONAL FINISHES:**

- B Polished Brass
- D Polished Chrome
- L Lead Coated
- W Wax Coated (200°F maximum)
- LW Wax Over Lead (200°F maximum)

**VARIATION: Specify**

- Small Orifice:  1/4"  5/16"  3/8"  7/16"
- Large Orifice:  3/4"

### PENDANT



**6110 SERIES**

Sprinkler is installed below the lateral piping.

Fig.	Degrees	Frame Color	Bulb Color
<input type="checkbox"/> 6111	155	Plain	Red
<input type="checkbox"/> 6112	200	White	Green
<input type="checkbox"/> 6113	280	Blue	Blue
<input type="checkbox"/> 6114	360	Red	Mauve

**WRENCH**


### UPRIGHT



**6120 SERIES**

Sprinkler is installed above the lateral piping.

Fig.	Degrees	Frame Color	Bulb Color
<input type="checkbox"/> 6121	155	Plain	Red
<input type="checkbox"/> 6122	200	White	Green
<input type="checkbox"/> 6123	280	Blue	Blue
<input type="checkbox"/> 6124	360	Red	Mauve



### HORIZONTAL SIDEWALL



**6130 SERIES**

Sprinkler is installed adjacent to juncture of ceiling and wall.

Fig.	Degrees	Frame Color	Bulb Color
<input type="checkbox"/> 6131	155	Plain	Red
<input type="checkbox"/> 6132	200	White	Green
<input type="checkbox"/> 6133	280	Blue	Blue
<input type="checkbox"/> 6134	360	Red	Mauve

Fig. 6147

Steel Wrench to install  
6110 Series  
6120 Series  
6130 Series

### CHROME RECESSED



**6141-6143**

Chrome plated sprinkler is installed below the lateral piping and recessed into the ceiling. Furnished with adjustable chrome plated recessed clip.

Fig.	Degrees	Frame Color	Bulb Color
<input type="checkbox"/> 6141	155	Chrome	Red
<input type="checkbox"/> 6142	200	Chrome	Green
<input type="checkbox"/> 6143	280	Chrome	Blue

**TOOL**





Fig. 6148

Steel Tool to install  
6141-6143 Models

### CONCEALED CEILING



**6144-6146**

Concealed ceiling sprinkler head unit is installed flush with finished ceiling. The unit is covered by a 3 1/2" dia. chrome cover plate, when fusing temperature is reached, the cover falls off and head is operational.

Fig.	Degrees	Frame Color
<input type="checkbox"/> 6144	135	Chrome
<input type="checkbox"/> 6145	165	Chrome
<input type="checkbox"/> 6146	212	Chrome

**TOOLS**




Fig. 6149

Steel Tools to install  
6144-6146

DATE

3-1-86

OPTIONAL - W White Cover.

FIGURE NUMBER

**6110-6146**