

# AUTOMATIC FIRE SPRINKLER HEADS AND ACCESSORIES

**FUNCTION:** Used to discharge a water pattern to control fire automatically. Actuated by a heat-sensitive, liquid-filled glass bulb.

**VARIATIONS:** Specify

– **Small Orifice** 1/4" / 0.6 cm, 5/16" / 0.7 cm, 3/8" / 0.9 cm, 7/16" / 1.1 cm

– **Large Orifice** 1 7/32" / 1.35 cm

**FINISHES:**

- Brass
- White
- Bright Brass
- Wax Over Lead
- Chrome-Plated
- Black
- Wax
- Lead-Coated

  	<p>Installed below the lateral piping.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Model No.</th> <th>Degrees</th> <th>Bulb Color</th> </tr> </thead> <tbody> <tr><td>6111</td><td>155</td><td>Red</td></tr> <tr><td>6112</td><td>200</td><td>Green</td></tr> <tr><td>6113</td><td>286</td><td>Blue</td></tr> <tr><td>6114</td><td>360</td><td>Mauve</td></tr> </tbody> </table> <p style="text-align: center;">STANDARD RESPONSE</p>	Model No.	Degrees	Bulb Color	6111	155	Red	6112	200	Green	6113	286	Blue	6114	360	Mauve	  	<p>Installed above the lateral piping.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Model No.</th> <th>Degrees</th> <th>Bulb Color</th> </tr> </thead> <tbody> <tr><td>6121</td><td>155</td><td>Red</td></tr> <tr><td>6122</td><td>200</td><td>Green</td></tr> <tr><td>6123</td><td>286</td><td>Blue</td></tr> <tr><td>6124</td><td>360</td><td>Mauve</td></tr> </tbody> </table> <p style="text-align: center;">STANDARD RESPONSE</p>	Model No.	Degrees	Bulb Color	6121	155	Red	6122	200	Green	6123	286	Blue	6124	360	Mauve									
Model No.	Degrees	Bulb Color																																								
6111	155	Red																																								
6112	200	Green																																								
6113	286	Blue																																								
6114	360	Mauve																																								
Model No.	Degrees	Bulb Color																																								
6121	155	Red																																								
6122	200	Green																																								
6123	286	Blue																																								
6124	360	Mauve																																								
  	<p>Operates up to 7 times faster than standard response sprinklers.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Model No.</th> <th>Degrees</th> <th>Bulb Color</th> </tr> </thead> <tbody> <tr><td>6110 Q</td><td>135</td><td>Orange</td></tr> <tr><td>6111 Q</td><td>155</td><td>Red</td></tr> <tr><td>6112 Q</td><td>175</td><td>Yellow</td></tr> <tr><td>6113 Q</td><td>200</td><td>Green</td></tr> <tr><td>6114 Q</td><td>286</td><td>Blue</td></tr> </tbody> </table> <p style="text-align: center;">QUICK RESPONSE</p>	Model No.	Degrees	Bulb Color	6110 Q	135	Orange	6111 Q	155	Red	6112 Q	175	Yellow	6113 Q	200	Green	6114 Q	286	Blue	  	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Model No.</th> <th>Degrees</th> <th>Bulb Color</th> </tr> </thead> <tbody> <tr><td>6120 Q</td><td>135</td><td>Orange</td></tr> <tr><td>6121 Q</td><td>155</td><td>Red</td></tr> <tr><td>6122 Q</td><td>175</td><td>Yellow</td></tr> <tr><td>6123 Q</td><td>200</td><td>Green</td></tr> <tr><td>6124 Q</td><td>286</td><td>Blue</td></tr> </tbody> </table> <p style="text-align: center;">QUICK RESPONSE</p>	Model No.	Degrees	Bulb Color	6120 Q	135	Orange	6121 Q	155	Red	6122 Q	175	Yellow	6123 Q	200	Green	6124 Q	286	Blue			
Model No.	Degrees	Bulb Color																																								
6110 Q	135	Orange																																								
6111 Q	155	Red																																								
6112 Q	175	Yellow																																								
6113 Q	200	Green																																								
6114 Q	286	Blue																																								
Model No.	Degrees	Bulb Color																																								
6120 Q	135	Orange																																								
6121 Q	155	Red																																								
6122 Q	175	Yellow																																								
6123 Q	200	Green																																								
6124 Q	286	Blue																																								
  	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Model No.</th> <th>Degrees</th> <th>Bulb Color</th> </tr> </thead> <tbody> <tr><td>6130 Q</td><td>135</td><td>Orange</td></tr> <tr><td>6131 Q</td><td>155</td><td>Red</td></tr> <tr><td>6132 Q</td><td>175</td><td>Yellow</td></tr> <tr><td>6133 Q</td><td>200</td><td>Green</td></tr> <tr><td>6134 Q</td><td>286</td><td>Blue</td></tr> </tbody> </table> <p style="text-align: center;">QUICK RESPONSE</p>	Model No.	Degrees	Bulb Color	6130 Q	135	Orange	6131 Q	155	Red	6132 Q	175	Yellow	6133 Q	200	Green	6134 Q	286	Blue	  	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Model No.</th> <th>Degrees</th> <th>Bulb Color</th> </tr> </thead> <tbody> <tr><td>6130</td><td>135</td><td>Orange</td></tr> <tr><td>6131</td><td>155</td><td>Red</td></tr> <tr><td>6132</td><td>175</td><td>Yellow</td></tr> <tr><td>6133</td><td>200</td><td>Green</td></tr> <tr><td>6134</td><td>286</td><td>Blue</td></tr> <tr><td>6135</td><td>360</td><td>Mauve</td></tr> </tbody> </table> <p style="text-align: center;">STANDARD RESPONSE</p>	Model No.	Degrees	Bulb Color	6130	135	Orange	6131	155	Red	6132	175	Yellow	6133	200	Green	6134	286	Blue	6135	360	Mauve
Model No.	Degrees	Bulb Color																																								
6130 Q	135	Orange																																								
6131 Q	155	Red																																								
6132 Q	175	Yellow																																								
6133 Q	200	Green																																								
6134 Q	286	Blue																																								
Model No.	Degrees	Bulb Color																																								
6130	135	Orange																																								
6131	155	Red																																								
6132	175	Yellow																																								
6133	200	Green																																								
6134	286	Blue																																								
6135	360	Mauve																																								
  	<p>Early Suppression/Fast Response</p> <ul style="list-style-type: none"> <li>• Plain brass pendent only</li> <li>• Ideal for warehouse installation</li> <li>• Suppress rather than control fire</li> <li>• 155° and 200° rating</li> </ul>	  	<p>Extended Coverage Quick Response</p> <ul style="list-style-type: none"> <li>• Economy</li> <li>• Reduced piping</li> <li>• Light hazard</li> <li>• Maximum room size 16' x 24' / 4.9 m x 7.1 m</li> <li>• 135° rating</li> </ul>																																							

Call Potter-Roemer for current listings and approvals. Dimensions are subject to manufacturer's tolerance and change without notice. We assume no responsibility for use of superseded or void data.



# SPRINKLER ACCESSORIES AND TESTING EQUIPMENT

## CANOPY



### Size

- Model 6152 ..... 2 1/4" / 5.7 cm Long
  - Model 6154 ..... 4" / 10.2 cm Long
  - Model 6156 ..... 6" / 15.2 cm Long
  - Model 6158 ..... Adjustable 2"-3" / 5-7.6 cm
- Polished aluminum with weep hole. Used to conceal and trim pipe penetration of finished ceiling. Depth as selected by Model Number.

## SPARE HEAD BOX



- Model 6162**  
Red glossy polyester coated steel box used to store sprinklers for emergency replacement. Will accommodate a maximum of twelve 1/2" / 1.2 cm or 3/8" / 1.35 cm heads (or 6-ESFR heads) and sprinkler wrench.

## TEST AND DRAIN



### Size

- Model 6166 ..... 3/4" / 1.9 cm
  - Model 6167 ..... 1" / 2.5 cm
  - Model 6168 ..... 1 1/4" / 3.2 cm
  - Model 6169 ..... 1 1/2" / 3.8 cm
  - Model 6170 ..... 2" / 5 cm
- Forged brass Female x Female body with spring loaded position indicator with positive shut off. In-line flow with self-draining, clearable sight glass. Tamper-proof orifice permanently installed.

## PITOT TUBE




- Model 6177**  
CHROME PLATED 16 1/2" / 41.9 cm long tube with rubber grip and 200 lb. / 138 bars liquid-filled pressure gauge, in 2 lb. / 0.9 kg increments. Used to conduct residual pressure and flow tests on standpipe and sprinkler systems. Furnished with computation table.
- OPTION: -C** White glossy polyester coated carrying case with foam lining.

## GUARD



- Model 6160**  
Red painted wire cage used for sprinkler head protection.


## BAFFLE



- Model 6165**  
Galvanized steel, used to prevent open sprinkler from cooling adjoining sprinklers when spaced less than 6' / 1.8 m apart.  
**SPECIFY:** Size required

## LINE TESTER



- Model 6175**   
Forged brass body, 1" / 2.5 cm female NPT inlet x 1/2" / 1.2 cm female outlet (sprinkler head) x 1" / 2.5 cm NPSH drain outlet with cap and chain and wrench-operated shutoff. Installed with the last sprinkler head on system branch lines. Controls water flow for flushing or testing of the system.

## TESTING EQUIPMENT



Used to conduct pressure tests on standpipe or sprinkler systems. Size and type as selected by Model Number.

- | ADAPTER TYPE | Size                  | CAP TYPE   | Size                  |
|--------------|-----------------------|------------|-----------------------|
| Model 6181   | ..... 1 1/2" / 3.8 cm | Model 6183 | ..... 1 1/2" / 3.8 cm |
| Model 6182   | ..... 2 1/2" / 6.4 cm | Model 6184 | ..... 2 1/2" / 6.4 cm |
- Female swivel hose thread x male hose thread.  
Female hose thread with pet cock.  
**SPECIFY:** Threads