



1300 SERIES FIRE HOSE CABINETS


FOR USE WITH: 1-1/2" FIRE HOSE RACK ASSEMBLY • PORTABLE FIRE EXTINGUISHER




RECESSED



TRIMLESS



SEMI-RECESSED



SURFACE

18 ga. Steel Box
Furnished less
Knockouts

REGULARLY FURNISHED: 20ga. box; 20 ga. tubular steel door with 18 ga. frame and a continuous steel hinge. All components are powder-coated with an electrostatically-applied, thermally-fused, recoatable white polyester finish. All glass door styles provided with clear tempered safety glass. Wall mounting and size of cabinet as selected by model number.

Model No.	Wall Mounting	Max. Capacity		Inside Box Dimensions			Overall Frame		Wall Opening Required			Trim	Inlet Location				ADA
		Poly flex ft.	Super flex ft.	K	L	M	N	O	W I D T H	H E I G H T	D E P T H		T	W	X	Y	
1302	Recessed	75	50	30	30	8	33 3/4	33 3/4	31	31	8 1/2	800	4	4	2 3/4	4	Yes
1304	Recessed	100	75	30	36	8	33 3/4	39 3/4	31	37	8 1/2	800	4	4	2 3/4	4	Yes
1306	Recessed	100	100	30	40	8	33 3/4	43 3/4	31	41	8 1/2	800	4	4	2 3/4	4	Yes
1312	Trimless	75	50	30	30	8	33	33	31	31	9 1/4	-	4	4	2 3/4	4	Yes
1314	Trimless	100	75	30	36	8	33	39	31	37	9 1/4	-	4	4	2 3/4	4	Yes
1316	Trimless	100	100	30	40	8	33	43	31	41	9 1/4	-	4	4	2 3/4	4	Yes
1332	Semi-Recessed	75	50	30	30	8	33 1/4	32 1/4	31	31	5 3/4	2 3/4	4	4	2 3/4	4	Yes
1334	Semi-Recessed	100	75	30	36	8	33 1/4	38 1/4	31	37	5 3/4	2 3/4	4	4	2 3/4	4	Yes
1336	Semi-Recessed	100	100	30	40	8	33 1/2	43 1/2	31	41	5 3/4	2 3/4	4	4	2 3/4	4	Yes
1342	Semi-Recessed	75	50	30	30	8	33 1/4	32 1/4	31	31	3 3/4	4 3/4	4	4	2 3/4	4	No
1344	Semi-Recessed	100	75	30	36	8	33 1/4	38 1/4	31	37	3 3/4	4 3/4	4	4	2 3/4	4	No
1346	Semi-Recessed	100	100	30	40	8	33 1/2	43 1/2	31	41	3 3/4	4 3/4	4	4	2 3/4	4	No
1352	Surface	75	50	32	32	9 1/4	-	-	-	-	-	9 1/4	-	-	-	-	No
1354	Surface	100	75	32	38	9 1/4	-	-	-	-	-	-	-	-	-	-	No
1356	Surface	100	100	32	42	9 1/4	-	-	-	-	-	-	-	-	-	-	No

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED

- OPTIONAL DOOR & FRAME MATERIAL**
- (AL-) **ALUMINUM:** Clear anodized finish
 - (SS-) **STAINLESS STEEL:** No. 304 stainless, with No. 4 finish.
 - (PB-) **BRASS:** Polished finish
 - (BZ-) **BRONZE:** Call for options
- OPTIONAL FINISHES**
- (AL-) **ALUMINUM:** Duranodic finish (specify)
 - Light Medium Dark
 - (SS6-) **STAINLESS STEEL:** Finish as specified
 - No. 304 stainless, with No. 6 dull satin finish
 - No. 304 stainless, with No. 8 mirror finish
 - (-RED) **RED** Powder-Coat
 - Custom Colors (specify)

- CABINET MODIFICATIONS**
- Dana Type: Frameless, Concealed-Hinge Construction
 - (-HF) Horizontal Fold Cabinet
 - (-DP) Duplex Cabinet
- DOOR STYLES**
- Full Glass, w/Tempered Safety Glass -A
 - Full Glass, w/Lock & Break Rite® Handle -B
 - Duo-Panel w/Tempered Safety Glass -D
 - Duo-Vertical Panel w/Tempered Safety Glass -DV
 - Duo-Vertical Panel w/ Lock, TSG & Break Rite® Handle -DVL
 - Tempered Safety Glass (25 sq. in.) w/Break Rite® Handle -E
 - Flush Solid Metal -F
 - Flush Solid Metal w/ Lock -FS
 - Inset Panel -J
 - Optional inserts for glass-style doors (specify)
- SUFFIX**

NOTE: Door Styles -A, -D, -DV, -F, & -J provided w/lever handle/cam latch. All Glass Door Styles Provided With Clear Tempered Safety Glass, In Compliance With ANSI#Z97.1-1984

Job Name: _____
 Architect/Contractor: _____
 Rep: _____
 Page: _____ of _____

DATE:
August 2009




MODEL NUMBER
1300 SERIES


FIRE RATED • UL CLASSIFIED 7N43

FRC1300 SERIES FIRE HOSE CABINETS


FOR USE WITH: 1-1/2" FIRE HOSE RACK ASSEMBLY • PORTABLE FIRE EXTINGUISHER




REGULARLY FURNISHED: CLASSIFIED BY UNDERWRITERS LABORATORIES INC. for use in the through penetration firestop systems. The applicable rating information is listed at 2 hours for flame, temperature, and/or hose stream. A 20ga. Box, with knock out provision in inner box; (penetration of fire protection box, to accommodate piping, and the restoration of fire stop around penetration, shall be completed by installing contractor). 20 ga. tubular steel door with 18 ga. frame and a continuous steel hinge. All components are powder-coated with an electrostatically-applied, thermally-fused, recoatable white polyester finish. All glass door styles provided with clear tempered safety glass. Wall mounting and size of cabinet as selected by model number.



RECESSED



TRIMLESS



SEMI-RECESSED

Note: Fire-Rated Surface-Mounted cabinets are not offered because there is no penetration of the wall.

Job Name: _____

Architect/Contractor: _____

Rep: _____

Page: _____ of _____

Model No.	Wall Mounting	Max. Capacity		Inside Box Dimensions			Overall Frame		Wall Opening Required			Trim	Inlet Location			
		Poly flex ft.	Super flex ft.	K	L	M	N	O	W I D T H	H E I G H T	D E P T H		T	W	X	Y
FRC1302	Recessed	75	50	30	30	8	33 ³ / ₄	33 ³ / ₄	32 ¹ / ₄	32	9 ¹ / ₈	OPTION	4	4	2 ³ / ₄	4
FRC1304	Recessed	100	75	30	36	8	33 ³ / ₄	39 ³ / ₄	32 ¹ / ₄	38	9 ¹ / ₈	OPTION	4	4	2 ³ / ₄	4
FRC1306	Recessed	100	100	30	40	8	33 ³ / ₄	43 ³ / ₄	32 ¹ / ₄	42	9 ¹ / ₈	OPTION	4	4	2 ³ / ₄	4
FRC1312	Trimless	75	50	30	30	8	33	33	32 ¹ / ₄	32	10 ¹ / ₂	-	4	4	2 ³ / ₄	4
FRC1314	Trimless	100	75	30	36	8	33	39	32 ¹ / ₄	38	10 ¹ / ₂	-	4	4	2 ³ / ₄	4
FRC1316	Trimless	100	100	30	40	8	33	43	32 ¹ / ₄	42	10 ¹ / ₂	-	4	4	2 ³ / ₄	4
FRC1332	Semi-Recessed	75	50	30	30	8	33 ¹ / ₂	33 ¹ / ₂	32 ¹ / ₄	32	7	2 ³ / ₄	4	4	2 ³ / ₄	4
FRC1334	Semi-Recessed	100	75	30	36	8	33 ¹ / ₂	39 ¹ / ₂	32 ¹ / ₄	38	7	2 ³ / ₄	4	4	2 ³ / ₄	4
FRC1336	Semi-Recessed	100	100	30	40	8	33 ¹ / ₂	43 ¹ / ₂	32 ¹ / ₄	42	7	2 ³ / ₄	4	4	2 ³ / ₄	4
FRC1342	Semi-Recessed	75	50	30	30	8	33 ¹ / ₂	33 ¹ / ₂	32 ¹ / ₄	32	5	4 ³ / ₄	4	4	2 ³ / ₄	4
FRC1344	Semi-Recessed	100	75	30	36	8	33 ¹ / ₂	39 ¹ / ₂	32 ¹ / ₄	38	5	4 ³ / ₄	4	4	2 ³ / ₄	4
FRC1346	Semi-Recessed	100	100	30	40	8	33 ¹ / ₂	43 ¹ / ₂	32 ¹ / ₄	42	5	4 ³ / ₄	4	4	2 ³ / ₄	4

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED

OPTIONAL DOOR & FRAME MATERIAL

- (AL-) **ALUMINUM:** Clear anodized finish
- (SS-) **STAINLESS STEEL:** No. 304 stainless, with No. 4 finish.
- (PB-) **BRASS:** Polished finish
- (BZ-) **BRONZE:** Call for options

OPTIONAL FINISHES

- (AL-) **ALUMINUM:** Duranodic finish (specify)
 - Light Medium Dark
- (SS6-) **STAINLESS STEEL:** Finish as specified
 - No. 304 stainless, with No. 6 dull satin finish
- (SS8-) **STAINLESS STEEL:** Finish as specified
 - No. 304 stainless, with No.8 mirror finish
- (-RED) **RED** Powder-Coat
- Custom Colors (specify)

CABINET MODIFICATIONS

- Dana Type: Frameless, Concealed-Hinge Construction
- (-HF) Horizontal Fold Cabinet
- (-DP) Duplex Cabinet

DOOR STYLES

- Full Glass, w/Tempered Safety Glass -A
- Full Glass, w/Lock & Break Rite® Handle -B
- Duo-Panel w/Tempered Safety Glass -D
- Duo-Vertical Panel w/Tempered Safety Glass -DV
- Duo-Vertical Panel w/ Lock, TSG & Break Rite® Handle -DVL
- Tempered Safety Glass (25 sq. in.) w/Break Rite® Handle -E
- Flush Solid Metal -F
- Flush Solid Metal w/ Lock -FS
- Inset Panel -J

NOTE: Door Styles -A, -D, -DV, -F, & -J provided w/lever handle/cam latch.

All Glass Door Styles Provided With Clear Tempered Safety Glass, In Compliance With ANSI#Z97.1-1984



MODEL NUMBER
FRC1300 SERIES