




CONSTANT FLOW FOG NOZZLES

BRASS SINGLE GALLONAGE NOZZLES



REGULARLY FURNISHED: Cast brass nozzle with polished finish. Integral ball shut off with horseshoe handle. Positive grip rubber bumper, swivel base. Size as selected by Figure Number.

Fig.	Size	G.P.M.
<input type="checkbox"/> 2991	3/4"	20
<input type="checkbox"/> 2992	1"	20
<input type="checkbox"/> 2993	1 1/2"	100
<input type="checkbox"/> 2994	2 1/2"	250

OPTIONAL FINISH: —D Polished Chrome

THREADS: NST
 OTHER _____

ALUMINUM SINGLE GALLONAGE NOZZLE



REGULARLY FURNISHED: Lightweight aluminum alloy nozzle with hard anodized finish. Integral ball shut-off with horseshoe handle: Positive grip rubber bumper, swivel base.


Fig. 2995 1 1/2" size (95 G.P.M.).

OPTIONAL: 60 or 125 G.P.M., specify.

THREADS AVAILABLE:

- NST
- NPSH

ALUMINUM ADJUSTABLE GALLONAGE NOZZLES



REGULARLY FURNISHED: Lightweight aluminum alloy nozzle with hard anodized finish. Integral ball shut-off with horseshoe handle. Positive grip rubber bumper, swivel base. Gallonage adjustments of 30, 60, 95, 125, 150, 180, and 200 G.P.M.

- Fig. 2996** 1 1/2" size
- 2997** 1 1/2" size with integral pistol grip.

For use with 1/2", 3/4", and 2" hose lines with 1/2" threads.

THREADS AVAILABLE:

- NST
- NPSH

NOTE ON AFFF: When used for aqueous film forming foam (AFFF) application, nozzles Figure Number, 2995, 2996, and 2997 must be used with an eductor of equal gallonage rating. Contact Potter-Roemer for application assistance.

FOG NOZZLE DISCHARGE DATE

Nozzle Position	PSI	Nozzle Figure Number															125 G.P.M. Adj.	
		2959	2960	2961	2962	2971	2972	2973	2974	2980	2985	2991	2992	2993	2994	2995	2996	2997
Straight Stream	50	15	38	83	45	18	45	90	90	—	—	14	14	70	175	57	80	80
	75	20	48	101	50	22	50	100	100	—	—	17	17	85	215	80	100	100
	100	22	71	118	55	24	55	100	110	—	—	20	20	100	250	95	125	125
30° Fog	50	15	52	119	50	21	50	120	120	56	45	14	14	70	175	57	80	80
	75	20	62	150	55	25	55	140	140	62	55	17	17	85	215	80	100	100
	100	22	71	170	60	28	60	165	165	79	65	20	20	100	250	95	125	125
60° Fog	50	15	52	119	55	24	55	130	130	52	55	14	14	70	175	57	80	80
	75	20	62	150	65	28	65	150	150	62	65	17	17	85	215	80	100	100
	100	22	71	170	75	32	75	180	180	78	75	20	20	100	250	95	125	125
90° Fog	50	15	51	138	60	27	60	145	145	56	65	14	14	70	175	57	80	80
	75	20	60	168	75	32	75	180	180	62	75	17	17	85	215	80	100	100
	100	22	71	195	80	36	80	205	205	77	85	20	20	100	250	95	125	125
Full Fog	50	15	51	138	75	30	75	200	200	56	70	14	14	70	175	57	80	80
	75	20	62	168	85	35	85	236	230	62	80	17	17	85	215	80	100	100
	100	22	71	195	90	41	90	275	275	77	90	20	20	100	250	95	125	125

Flow in gallons per minute

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE. WE ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA.