



A Division of Smith Industries, Inc.



Call Potter-Roemer for current listings and approvals. Dimensions are subject to manufacturers tolerance and change without notice. We assume no responsibility for use of superseded or void data.

FIRE HOSE

NOTE: All Hoses Normally Supplied With Couplings Attached.

SINGLE JACKET HOSE

300 lb. TEST

REGULARLY FURNISHED:

100% polyester jacket and synthetic rubber lining. ◀ FM ▶ label. Size as selected by Figure Number.



✓ Fig. No.	Coupling Size	Hose I.D.	Hose O.D.	Coupling
*2901	1 1/2"	1 1/2"	1 3/4"	2934
*2902	2 1/2"	2 1/2"	2 13/16"	2936

AVAILABLE:

- 50' 75' 100' lengths

OPTIONS:

- U/L Label
 Neoprene Impregnation
 Hypalon Impregnation

600 lb. TEST

REGULARLY FURNISHED:

100% polyester jacket and synthetic rubber lining. Designed for more resistance to many acids, alkalines and other chemicals. Used where working pressures are higher than normal ◀ FM ▶ label. Size as selected by Figure Number.

✓ Fig. No.	Coupling Size	Hose I.D.	Hose O.D.	Coupling
2903	1 1/2"	1 1/2"	1 3/4"	2934
2904	1 1/2"	1 3/4"	1 15/16"	2942
2905	1 1/2"	2"	2 5/16"	2942-2 5/16
2906	2 1/2"	2 1/2"	2 13/16"	2936

VARIATION:

- N Neoprene lining


THREADS:

- N.S.T.
 Other _____



DOUBLE JACKET HOSE 600 lb. TEST

REGULARLY FURNISHED: 100% polyester double jacket and synthetic rubber lining. ◀ FM ▶ label. Size as selected by Figure Number.



✓ Fig. No.	Coupling Size	Hose I.D.	Hose O.D.	Coupling
*2911	1 1/2"	1 1/2"	1 15/16"	2938
*2912	1 1/2"	1 3/4"	2 1/8"	2942-2 1/8
2913	1 1/2"	2"	2 9/16"	2942-2 9/16
2914	2 1/2"	2 1/2"	3"	2937

AVAILABLE: 50' 75' 100' lengths

- OPTIONS:** U/L Label
 Neoprene Impregnation
 Hypalon Impregnation

VARIATION: -N Neoprene lining

THREADS: N.S.T. Other _____



RACK AND REEL HOSE 500 lb. TEST POLYFLEX

(FOR INTERIOR STANDPIPE)

REGULARLY FURNISHED: 100% synthetic jacket and extruded 100% synthetic lining ◀ FM ▶ label. Size as selected by Figure Number.



✓ Fig. No.	Coupling Size	Hose I.D.	Hose O.D.	Coupling
*2915	1 1/2"	1 1/2"	1 11/16"	2930
2916	2 1/2"	2 1/2"	2 13/16"	2936

AVAILABLE: 50' 75' 100' lengths

OPTIONS: U/L Label 300 TEST

THREADS: N.S.T. Other _____



100% SYNTHETIC totally immune to mildew and rot, never needs drying.
100% PLYESTER — will not mildew or decay with age. Resistant to many acids.

DATE
9-1-86

NOTE: ALWAYS INDICATE HOSE THREAD REQUIREMENTS

FIGURE NUMBER

2901-2916




Call Potter-Roemer for current listings and approvals. Dimensions are subject to manufacturers tolerance and change without notice. We assume no responsibility for use of superseded or void data.

FIRE HOSE

NOTE: All Hoses Normally Supplied With Couplings Attached.

RUBBER COVERED HOSE 400 lb. TEST

REGULARLY FURNISHED: 100% polyester jacket and synthetic rubber lining with spirally wrapped synthetic rubber outer covering. Size as selected by figure number.



✓ Fig. No.	Coupling Size	Hose I.D.	Hose O.D.	Coupling
2917	1½"	1½"	1 13/16"	2935
2918	1½"	2"	2 5/16"	2942-2 5/16
2919	2½"	2½"	2 13/16"	2936


AVAILABLE: 50' length

THREADS: N.S.T. Other _____

VARIATION: -N Neoprene lining

NEOPRENE COVERED HOSE 400 lb. TEST

REGULARLY FURNISHED: 100% polyester jacket and synthetic rubber lining with spirally wrapped neoprene outer covering. Size as selected by Figure Number.



✓ Fig. No.	Coupling Size	Hose I.D.	Hose O.D.	Coupling
2920	1½"	1½"	1 13/16"	2935
2921	1½"	2"	2 5/16"	2942-2 5/16
2922	2½"	2½"	2 13/16"	2936

AVAILABLE: 50' length

THREADS: N.S.T. Other _____

VARIATION: -N Neoprene lining

RACK AND REEL HOSE 500 lb. TEST SUPER POLYFLEX

REGULARLY FURNISHED: 100% polyester jacket and synthetic rubber lining ◀FM▶ label. Size as selected by Figure Number.



✓ Fig. No.	Coupling Size	Hose I.D.	Hose O.D.	Coupling
*2926	1½"	1½"	1¾"	2934
*2927	1½"	1¾"	1 15/16"	2942
2928	1½"	2"	2 5/16"	2942-2 5/16
2929	2½"	2½"	2 13/16"	2936

AVAILABLE: 50' 75' 100' lengths

OPTIONS:

- U/L Label
- Neoprene Impregnation
- Hypalon Impregnation

THREADS: N.S.T. Other _____

VARIATION: -N Neoprene lining



HYPALON IMPREGNATION: Imparts excellent weathering properties and resistance to abrasion, heat, oil, and ozone.

Colors available: Red, Black, Yellow, Orange, Tan - Specify

NEOPRENE IMPREGNATION: Imparts superior resistance to ozone, heat, cold, and acids. Colors available: Red, Black - Specify

NEOPRENE LINING: Imparts superior resistance to ozone, heat, cold, and oils.

DATE

9-1-86

NOTE: ALWAYS INDICATE HOSE THREAD REQUIREMENTS

FIGURE NUMBER

2917-2929