

SPECIFICATIONS

RUBBER COVERED HOSE

400 lb. ACCEPTANCE TEST & 200 lb. SERVICE TEST - 100% polyester jacket and synthetic rubber lining with spirally wrapped synthetic rubber outer covering. Size as selected by model number.

NEOPRENE COVERED HOSE

400 lb. ACCEPTANCE TEST & 200 lb. SERVICE TEST - 100% polyester jacket and synthetic rubber lining with spirally wrapped synthetic rubber outer covering. Size as selected by model number.

RACK AND REEL SUPER POLYFLEX HOSE

500 lb. ACCEPTANCE TEST & 250 lb. SERVICE TEST - 100% polyester jacket and synthetic rubber lining with spirally wrapped synthetic rubber outer covering. Size as selected by model number.

MODEL SELECTION

RUBBER COVERED HOSE

- 2917
- 2918
- 2919

NEOPRENE COVERED HOSE

- 2920
- 2921
- 2922

RACK AND REEL SUPER POLYFLEX HOSE

- 2927
- 2928
- 2929



PRODUCT OPTIONS

LENGTHS:

- 50'
- 75' (Super Polyflex Models Only)
- 100' (Super Polyflex Models Only)

VARIATIONS:

- N Neoprene lining

OPTIONS: (Super Polyflex Models Only)

- U/L Label
- Neoprene Impregnation
- Hypalon Impregnation

THREADS:

- N.S.T.
- Other _____

HYPALON IMPREGNATION: Imparts excellent weathering properties and resistance to abrasion, heat, oil, and ozone. Colors available: Red, Black, Yellow, Orange, Tan - Specify

NEOPRENE IMPREGNATION: Imparts superior resistance to ozone, heat, cold, and acids. Colors available: Red, Black - Specify

NEOPRENE LINING: Imparts superior resistance to ozone, heat, cold, and oils.

NOTE: ALWAYS INDICATE HOSE THREAD REQUIREMENTS

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superseded data. © Copyright Potter Roemer - Fire Pro, Member of Morris Group International™ Please visit potterroemer.com for most current specifications.

2917-2929 SERIES Date: 05/06/19

MEMBERSHIP



FIRE EQUIPMENT
MANUFACTURERS'
ASSOCIATION




POTTER ROEMER/FIRE PRO


Headquarters:
P.O. Box 3527
City of Industry, CA
91744 U.S.A.
Los Angeles Area
800-366-3473
626-855-4890


Also in:
New York (800) 526-4592
Chicago (800) 547-3473
Atlanta (800) 762-0542
Miami (866) 961-3473
Dallas (866) 644-3473

www.potterroemer.com

MODEL SELECTION

Model No.	Coupling Size	Hose I.D.	Hose O.D.	Coupling
Rubber Covered Hose				
2917	1-1/2"	1-1/2"	1-13/16"	2935
2918	1-1/2"	2"	2-5/16"	2942 -2-5/16
2919	2-1/2"	2-1/2"	2-13/16"	2936
				

Model No.	Coupling Size	Hose I.D.	Hose O.D.	Coupling
Neoprene Covered Hose 400 lb. Test				
2920	1-1/2"	1-1/2"	1-13/16"	2935
2921	1-1/2"	2"	2-5/16"	2942 -2-5/16
2922	2-1/2"	2-1/2"	2-13/16"	2936
				

Model No.	Coupling Size	Hose I.D.	Hose O.D.	Coupling
Rack and Reel Super Polyflex Hose 500 lb. Test				
2927	1-1/2"	1-3/4"	1-15/16"	2942
2928	1-1/2"	2"	2-5/16"	2942 -2-5/16
2929	2-1/2"	2-1/2"	2-13/16"	2936
				



Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superseded data. © Copyright Potter Roemer - Fire Pro, Member of Morris Group International™ Please visit potterroemer.com for most current specifications.

2917-2929 SERIES Date: 05/06/19

MEMBERSHIP



FIRE EQUIPMENT
MANUFACTURERS'
ASSOCIATION



POTTER ROEMER/FIRE PRO

Headquarters:
P.O. Box 3527
City of Industry, CA
91744 U.S.A.
Los Angeles Area
800-366-3473
626-855-4890

Also in:
New York (800) 526-4592
Chicago (800) 547-3473
Atlanta (800) 762-0542
Miami (866) 961-3473
Dallas (866) 644-3473

www.potterroemer.com