

SPECIFICATIONS

HALOTRON 1

Red glossy polyester coated steel cylinder with bracket. The stored pressure environment friendly HCFC-123 "Clean Agent" is non-conductive, non-corrosive and rapidly evaporates leaving no residue. Recommended for electrical equipment fires.

CARBON DIOXIDE (Co2)

Red glossy polyester coated aluminum cylinder with discharge horn and wall bracket. Pressurized content is a non-contaminating odorless gas. Model 3405NM non-magnetic with white paint finish for use in MRI facilities.



PRODUCT OPTIONS

SEE 3900 SERIES CATALOG SECTION FOR OPTIONAL
FIRE EXTINGUISHER MOUNTING BRACKETS

MODEL SELECTION

- 3101 ABC 1.4# Halotron 1
- 3102 ABC 2.5# Halotron 1
- 3105 ABC 5# Halotron 1
- 3111 ABC 11# Halotron 1
- 3115 ABC 15.5# Halotron 1
- 3405 5# Carbon Dioxide
- 3405NM 5# Carbon Dioxide Non-Magnetic
- 3410 10# Carbon Dioxide
- 3415 15# Carbon Dioxide
- 3420 20# Carbon Dioxide

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer-Fire Pro assumes no responsibility for use of void or superceded data. © Copyright Potter Roemer- Fire Pro, Member of Morris Group International™ Please visit potterroemer.com for most current specifications.

3100/3400 SERIES Date: 5/28/20

MEMBERSHIP



FIRE EQUIPMENT
MANUFACTURERS'
ASSOCIATION

ONFSA
NATIONAL IRRE SPRINKLER ASSOCIATION, INC.



CASPE
American Society of
Plumbing Engineers



POTTER ROEMER/FIRE PRO

Headquarters:
P.O. Box 3527
City of Industry, CA
91744 U.S.A.
Los Angeles Area
800-366-3473
626-855-4890

Also in:
New York (800) 526-4592
Chicago (800) 547-3473
Atlanta (800) 762-0542
Miami (833) 744-3473
Dallas (866) 644-3473

www.potterroemer.com

MODEL DIMENSIONS

HALOTRON 1							
Model No.	Size lbs./kg	U/L Rating	Overall Height in./cm	Dia. In. / cm	Overall Width in./cm	Range of Stream ft./m	Type Discharge
3101	1.4 / .63	1B:C	10" / 25.4	2-5/8" / 6.6	3-1/2" / 8.9	6'-8" / 1.8-2.4	Nozzle
3102	2.5 / 1.1	2B:C	15-1/2" / 39.4	3" / 7.6	6-3/8" / 16.1	6'-10" / 1.8-3	Nozzle
3105	5 / 2.2	5B:C	15-1/4" / 38.7	4-1/4" / 10.8	5-3/4" / 14.6	9'-15' / 2.7-4.6	Nozzle
3111	11 / 5	1A:10B:C	21-7/8" / 55.5	6" / 15.2	9-1/4" / 23.5	9'-15' / 2.7-4.6	Hose & Nozzle
3115	15.5 / 7	2A:10B:C	21-7/8" / 55.5	6" / 15.2	9-1/4" / 23.5	12'-18' / .36-5.4	Hose & Nozzle



CARBON DIOXIDE (CO ₂)							
Model No.	Size lbs./kg	U/L Rating	Overall Height in./cm	Dia. In./cm	Overall Width in./cm	Range of Stream ft./m	Type Discharge
3405	5 / 2.3	5B:C	17-3/4" / 45	5-1/4" / 13.3	8-1/4" / 20.9	3'-8" / .91-2.4	Horn
3405NM*	5 / 2.3	5B:C	17-3/4" / 45	5-1/4" / 13.3	8-1/4" / 20.9	3'-8" / .91-2.4	Horn
3410	10 / 4.5	10B:C	24" / 61	7" / 17.8	12" / 30.4	3'-8" / .91-2.4	Hose & Horn
3415	15 / 6.8	10B:C	30" / 76.2	7" / 17.8	12" / 30.4	3'-8" / .91-2.4	Hose & Horn
3420	20 / 9	10B:C	30" / 76.2	8" / 20.3	13" / 33	3'-8" / .91-2.4	Hose & Horn



* Non-Magnetic approved for use in MRI facilities.

<p>Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer-Fire Pro assumes no responsibility for use of void or superceded data. © Copyright Potter Roemer- Fire Pro, Member of Morris Group International™ Please visit potterroemer.com for most current specifications.</p> <p>3100/3400 SERIES</p>	<p>MEMBERSHIP</p> 	<p>POTTER ROEMER/FIRE PRO</p> <p>Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890</p> <p>Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (833) 744-3473 Dallas (866) 644-3473</p> <p>www.potterroemer.com</p>
--	---	---