

## SPECIFICATIONS

**GROOVED ADAPTERS**, brass, used to change threaded fire department connections inlet/outlet to a grooved connection.

**OPEN SNOOTS**, cast brass construction with size and type of inlet and outlet as selected by model number. 300 psi rated.

**SPRING CHECK SNOOTS**, cast brass connection with pin lug swivel. Size and type as selected by model number. Polished brass exposed parts. 175 psi rated.

**CLAPPER CHECK SNOOTS**, cast brass connection with pin lug swivel. Size and type as selected by model number. Polished brass exposed parts. 300 psi rated.

## MODEL SELECTION

### GROOVED ADAPTERS

- ☐ 5900-GRV 4" M NPT x Groove
- ☐ 5900-6-GRV 6" M NPT x Groove

### OPEN SNOOTS

- ☐ 5902 2-1/2" F NPT Inlet x 2 1/2" M Hose Thread
- ☐ 5903 3" F NPT Inlet x 2 1/2" M Hose Thread
- ☐ 5905 3" F NPT Inlet x 3" M Hose Thread
- ☐ 5911 1-1/2" F Hose Thread x 1 1/2" M NPT Outlet
- ☐ 5912 2-1/2" F Hose Thread x 2 1/2" M NPT Outlet
- ☐ 5913 2-1/2" F Hose Thread x 3" M NPT Outlet
- ☐ 5915 3" F Hose Thread x 3" M NPT Outlet
- ☐ 5922 2-1/2" F Hose Thread x 2 1/2" F NPT Outlet
- ☐ 5923 2-1/2" F Hose Thread x 3" F NPT Outlet
- ☐ 5925 3" F Hose Thread x 3" F NPT Outlet

### SPRING CHECK SNOOTS WITH PIN LUG SWIVEL

- ☐ 5930 2-1/2" F Hose Inlet x 3" F NPT Outlet
- ☐ 5933 3" F Hose Inlet x 3" F NPT Outlet
- ☐ 5935 2-1/2" F Hose Inlet x 3" M NPT Outlet
- ☐ 5936 3" F Hose Inlet x 3" M NPT Outlet

### CLAPPER CHECK SNOOTS WITH SWIVEL INLET

- ☐ 5937 2-1/2" F Hose Inlet x 3" F NPT Outlet
- ☐ 5938 2-1/2" F Hose Inlet x 3" M NPT Outlet



MODEL 5922 (Shown)

## PRODUCT OPTIONS

### FINISHES:

- ☐ -B Polished Brass  
(Plugs and Chain Models Only)
- ☐ -C Rough Chrome Plated Body  
(Plugs and Chain Models Only)
- ☐ -D Polished Chrome Plated

### VARIATIONS: (Breakable Cap Models Only)

- ☐ -P Red plastic breakable cap 2-1/2" size
- ☐ -Plastic Red plastic plug and chain 2-1/2" size\*

### THREADS: (Not Available on Breakable Cap Models)

- ☐ N.S.T.
- ☐ Other \_\_\_\_\_

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superseded data. © Copyright Potter Roemer - Fire Pro, Member of Morris Group International™ Please visit [potterroemer.com](http://potterroemer.com) for most current specifications.

**5900-5938 SERIES** Date: 10/09/24

**MEMBERSHIP**



FIRE EQUIPMENT  
MANUFACTURERS'  
ASSOCIATION



**ONFSA**  
NATIONAL FIRE SPRINKLER ASSOCIATION, INC.



## POTTER ROEMER

Headquarters:  
P.O. Box 3527  
City of Industry, CA  
91744 U.S.A.  
Los Angeles Area  
800-366-3473  
626-855-4890

Also in:  
New York (800) 526-4592  
Chicago (800) 547-3473  
Atlanta (800) 762-0542  
Miami (833) 744-3473  
Dallas (866) 644-3473

[www.potterroemer.com](http://www.potterroemer.com)

## MODEL DIMENSIONS

### GROOVED ADAPTERS

### OPEN SNOOTS


Model No.	N.P.T. Inlet	Hose Outlet
5902	2-1/2"	2-1/2"
5903	3"	2-1/2"
5905	3"	3"



Female Inlet x Male Outlet

300 psi rated

Model No.	Hose Inlet	N.P.T. Outlet
5911	1-1/2"	1-1/2"
5912	2-1/2"	2-1/2"
5913	2-1/2"	3"
5915	3"	3"



Female Inlet x Male Outlet  
with Pin Lug Swivel

300 psi rated

Model No.	Hose Inlet	N.P.T. Outlet
5922	2-1/2"	2-1/2"
5923	2-1/2"	3"
5925	3"	3"



Double Female  
with Pin Lug Swivel


300 psi rated

### CHECK SNOOTS WITH PIN LUG SWIVEL

SPRING CHECK		
Model No.	Hose Inlet	N.P.T. Outlet
5930	2-1/2"	3" Female
5933	3"	3" Female
5935	2-1/2"	3" Male
5936	3"	3" Male




Double Female



Female Inlet x Male Outlet

175 psi rated



CLAPPER TYPE		
Model No.	Hose Inlet	N.P.T. Outlet
5937	2-1/2"	3" Female
5938	2-1/2"	3" Male




Double Female



Female Inlet x Male Outlet

300 psi rated



Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superseded data. © Copyright Potter Roemer - Fire Pro, Member of Morris Group International™ Please visit [potterroemer.com](http://potterroemer.com) for most current specifications.

**5902-5953 SERIES**

**MEMBERSHIP**



FIRE EQUIPMENT  
MANUFACTURERS'  
ASSOCIATION



**ONFSA**  
NATIONAL FIRE SPRINKLER ASSOCIATION, INC.



## POTTER ROEMER

Headquarters:  
P.O. Box 3527  
City of Industry, CA  
91744 U.S.A.  
Los Angeles Area  
800-366-3473  
626-855-4890

Also in:  
New York (800) 526-4592  
Chicago (800) 547-3473  
Atlanta (800) 762-0542  
Miami (833) 744-3473  
Dallas (866) 644-3473

[www.potterroemer.com](http://www.potterroemer.com)