

SPECIFICATIONS

TRAILER MOUNT

Single waterway monitor with red glossy polyester finish inside and out mounted on two wheel steel trailer with pneumatic tires, 1-7/8" ball hitch, red polyester finish, 2 - 2-1/2" brass NST female swivel inlets with drop clappers, 3" I.D. manifold, 2-1/2" NST outlet on monitor. Hose bed accommodates up to 200 feet of 2-1/2" double jacket hose. Rated gallonage as selected by model number. Less nozzle.

OSCILLATING

Single waterway monitor with red glossy polyester finish inside and out. Water driven oscillation with test connection and override to permit manual operation. adjustable 180° horizontal oscillation, cycle adjustable from 10-30 seconds. Rated gallonage as selected by model number. Less nozzle.

REMOTE CONTROL

Single waterway monitor with red glossy polyester finish inside and out. Carbon steel hydraulic cylinders to control vertical (90°) and horizontal (360°) movement. 1000 GPM automatic fog/straight stream nozzle. Braided stainless steel supply lines. Remote control station with 110 Volt A.C. or 220 Volt A.C., hydraulic power source. Single lever control for monitor movement and nozzle pattern adjustment. Rated gallonage of monitor as selected by model number.



MODEL 6426 (Shown)

PRODUCT OPTIONS

"NO AVAILABLE OPTIONS"

MODEL SELECTION

- ☐ **6416** Trailer Mount 750 GPM
- ☐ **6417** Trailer Mount 1200 GPM
- ☐ **6421** Oscillating 750 GPM
Specify Base: _____
- ☐ **6422** Oscillating 1200 GPM
Specify Base: _____
- ☐ **6426** Remote Control 750 GPM
☐ 110 Volt A.C. ☐ 220 Volt A.C.
- ☐ **6427** Remote Control 1200 GPM

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superseded data. © Copyright Potter Roemer - Fire Pro, Member of Morris Group International™ Please visit potterroemer.com for most current specifications.

6416-6427 SERIES Date: 09/20/18

MEMBERSHIP



FIRE EQUIPMENT
MANUFACTURERS'
ASSOCIATION



ONFSA
NATIONAL FIRE SPRINKLER ASSOCIATION, INC.



POTTER ROEMER/FIRE PRO

Headquarters:
P.O. Box 3527
City of Industry, CA
91744 U.S.A.
Los Angeles Area
800-366-3473
626-855-4890

Also in:
New York (800) 526-4592
Chicago (800) 547-3473
Atlanta (800) 762-0542
Miami (866) 961-3473
Dallas (866) 644-3473

www.potterroemer.com

MODEL DIMENSIONS

TRAILER MOUNT					
Model No.	Rated Gallonage	Size and type of Waterway	Trailer Size		
			Width	Height	Length
6416	750 GPM	2-1/2" Seamless	65"	54"	80"
6417	1200 GPM	3" Welded			



MODEL 6416-6417

OSCILLATING		
Model No.	Rated Gallonage	Size and type of Waterway
6421	750 GPM	2-1/2" Seamless
6422	1200 GPM	3" Welded

MONITOR AND BASE OPTIONS				
Waterway	G.P.M.	Model No.	Base Options	Available Bases
Single	750	6421	P-Q-R-S-W-X	P - 2-1/2" Male Q - 2-1/2" Female R - 3" Male S - 3" Female U - 4" Male W - 3" 125 lb. A.S.A. Flange X - 4" 125 lb. A.S.A. Flange
	1200	6422	R-S-W-X	



MODEL 6421-6422

REMOTE CONTROL			
Model No.	Rated Gallonage	Size and type of Waterway	Base
6426	750 GPM	2-1/2" Seamless	2-1/2" A.S.A. Flange
6427	1200 GPM	3" Welded	3" A.S.A. Flange



MODEL 6426-6427

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superseded data. © Copyright Potter Roemer - Fire Pro, Member of Morris Group International™ Please visit potterroemer.com for most current specifications.

6416-6427 SERIES Date: 09/20/18

MEMBERSHIP



FIRE EQUIPMENT
MANUFACTURERS'
ASSOCIATION



CASPE
American Society of
Plumbing Engineers

ONFSA
NATIONAL FIRE SPRINKLER ASSOCIATION, INC.



POTTER ROEMER/FIRE PRO

Headquarters:
P.O. Box 3527
City of Industry, CA
91744 U.S.A.
Los Angeles Area
800-366-3473
626-855-4890

Also in:
New York (800) 526-4592
Chicago (800) 547-3473
Atlanta (800) 762-0542
Miami (866) 961-3473
Dallas (866) 644-3473

www.potterroemer.com