

**SPECIFICATIONS**

Potter Roemer/ Fire Pro® Industrial Station monitors are ideal for withstanding extreme weather, industrial rigors, and petrochemical exposure often found in marine, offshore and industrial environments. Brass construction. Standard red powder coating gives a tough corrosion resistant finish.



**REGULARLY FURNISHED**

- 2-1/2" Waterway
- Brass construction
- 360° horizontal and 135° vertical travel
- 750 GPM (2839 lpm)

MODEL	INLET In (mm)	OUTLET In (mm)	HEIGHT In (mm)	WIDTH In (mm)	WEIGHT Lbs (kg)
FP10636-2	2-1/2" FLANGE (64)	2-1/2" (64)	18" (457)	14" (356)	44 (20)
FP10636-2F/2M	2-1/2" NPT (64)	2-1/2" (64)	18" (457)	14" (356)	44 (20)
FP10636-3	3" FLANGE (76)	2-1/2" (64)	18" (457)	14" (356)	44 (20)
FP10636-4	4" FLANGE (102)	2-1/2" (64)	18" (457)	14" (356)	44 (20)

⚠ WARNING: Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

<p>Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacture's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superceded data. Please visit <a href="http://potterroemer.com">potterroemer.com</a> for most current specifications</p> <p><b>FP10636</b></p> <p>Revised:09/04/18</p>	<p><b>MEMBERSHIP</b></p> 	<p><b>POTTER ROEMER/FIRE PRO</b></p> <p>Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890</p> <p>Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (866) 961-3473 Dallas (866) 644-3473</p> <p><a href="http://www.potterroemer.com">www.potterroemer.com</a></p>
--	---	---