

TILLER BAR MONITOR
1250 GPM FP10648 & FP10649

SPECIFICATIONS

Potter Roemer/ Fire Pro® Industrial Station monitors are ideal for withstanding extreme weather, industrial rigors, and petrochemical exposure often found in marine, offshore and industrial environments. Brass construction. Standard red powder coating gives a tough corrosion resistant finish.



REGULARLY FURNISHED

- 3" Waterway
- Brass construction
- 360° horizontal and 135° vertical travel for FP-10648 and 150° vertical travel for FP-10649
- 1250 GPM (4732 lpm)

MODEL	INLET In (mm)	OUTLET In (mm)	HEIGHT In (mm)	WIDTH In (mm)	WEIGHT Lbs (kg)
FP10648-3	3" FLANGE (76)	2-1/2" (64)	17" (432)	14" (356)	52 (24)
FP10648-3F	3" NPT (76)	2-1/2" (64)	17" (432)	14" (356)	52 (24)
FP10648-4	4" FLANGE (102)	2-1/2" (64)	17" (432)	14" (356)	52 (24)
FP10649-3	3" FLANGE (76)	2-1/2" (64)	17" (432)	14" (356)	56 (25)
FP10649-3F	3" NPT (76)	2-1/2" (64)	17" (432)	14" (356)	56 (25)
FP10649-4	4" FLANGE (102)	2-1/2" (64)	17" (432)	14" (356)	56 (25)

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

<p>Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacture's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superceded data. Please visit potterroemer.com for most current specifications</p> <p>FP10648 Revised:09/04/18</p>	<p>MEMBERSHIP</p>		<p>POTTER ROEMER/FIRE PRO</p> <p>Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890</p> <p style="text-align: right;">Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (866) 961-3473 Dallas (866) 644-3473</p> <p style="text-align: right;">www.potterroemer.com</p>
--	--------------------------	--	---