



1250 GPM

FP10736

SPECIFICATIONS

Potter Roemer/ Fire Pro® Industrial Station monitors are ideal for withstanding extreme weather, industrial rigors, and petrochemical exposure often found in marine, offshore and industrial environments. Brass construction. Standard red powder coating gives a tough corrosion resistant finish.



REGULARLY FURNISHED

- 2-1/2" Waterway
- Brass construction
- 360° horizontal and 135° vertical travel
- 1250 GPM (4732 lpm)

MODEL	INLET	OUTLET	HEIGHT	WIDTH	WEIGHT
	In (mm)	In (mm)	In (mm)	In (mm)	Lbs (kg)
FP10736-3	3" FLANGE (76)	2-1/2" (64)	18" (457)	18 " (457)	44 (20)
FP10736-3F	3" NPT	2-1/2"	18"	18 "	44
	(76)	(64)	(457)	(457)	(20)
FP10736-4	4" FLANGE (102)	2-1/2" (64)	18" (457)	18 " (457)	44 (20)

▲ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacture's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superceded data. Please visit potternoemer.com for most current specifications

















POTTER ROEMER/FIRE PRO

Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890 Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (866) 961-3473 Dallas (866) 644-3473

www.potterroemer.com