

SPECIFICATIONS

Potter Roemer/ Fire Pro® Oscillating Monitor conversion kits are designed for refineries, aircraft hangers, underwing and fuselage protection, fuel transfer areas, and any high-risk areas where unmanned coverage is essential. Brass and stainless steel construction. Standard red powder coating on flanges, gives a tough corrosion resistant finish.



REGULARLY FURNISHED

- 3" Waterway
- Brass and stainless steel construction
- Available with 3" (76mm) or 4" (102mm) ANSI flange
- Adjustable oscillation by 3 points @ 120°
- Maximum 1250 GPM (4732 lpm)
- Weight 85 Lbs (38.5 kg)

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

<p>Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacture's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superceded data. Please visit potterroemer.com for most current specifications</p> <p>FP10916</p> <p>Revised:09/04/18</p>	<p>MEMBERSHIP</p>       	<p>POTTER ROEMER/FIRE PRO</p> <p>Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890</p> <p>Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (866) 961-3473 Dallas (866) 644-3473</p> <p>www.potterroemer.com</p>
--	--	---