

SPECIFICATIONS

CLASSIFIED BY UNDERWRITERS LABORATORIES INC. for use in the through penetration fire stop systems. The applicable rating information is listed at 2 hours for flame, temperature, and/or hose stream. A galvannealed steel 20 ga. box; 20 ga. tubular door with 18 ga. frame and a continuous hinge. All components are powder-coated with an electrostatically-applied, thermally-fused, recoatable white polyester finish. Door is Flush Solid Metal with NYFD Yale lock.

MODEL DIMENSIONS

Model No.	Wall Mounting	Inside Box Dimensions			Overall Frame		Minimum Wall Opening Required			Trim	ADA
		к	L	М	N	0	W I D T H	H E I G H T	D E P T H	т	Ė
☐ FRC1302	Recessed	30	30	8	33-3/4	33-3/4	32-1/2	32	9-1/8	5/8	Yes





LOBBY CABINET EQUIPMENT

For buildings with 1 or 2 risers

☐ Model No. NYC-2000

Model No.	Part Description	□ 1 Riser □ QTY	2 Riser QTY
2915-50	1-1/2" Polyflex Hose 500 lb. Test 50'	2	4
2915-25	1-1/2" Polyflex Hose 500 lb. Test 25'	1	2
2930	1-1/2" Fire Hose Coupling NYFD Threads	3	6
2960NYFD	1-1/2" Lexan Fog Nozzle NYFD Threads	1	2
6050	1-1/2" Common Spanner	1	2
6051	2-1/2" Common Spanner	1	2
2810	2-1/2" NYFD F x 1-1/2" NYFD M Brass Hose Adapter	1	2

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer-Fire Pro assumes no responsibility for use of void or superceded data. © Copyright Potter Roemer-Fire Pro, Member of Morris Group International ™ Please visit potterroemer.com for most current specifications.













POTTER ROEMER/FIRE PRO

Headquarters: P.O. Box 3527 City of Industry, CA 91744 U.S.A. Los Angeles Area 800-366-3473 626-855-4890 Also in: New York (800) 526-4592 Chicago (800) 547-3473 Atlanta (800) 762-0542 Miami (833) 744-3473 Dallas (866) 644-3473

www.potterroemer.com