

### SPECIFICATIONS

Potter Roemer/ Fire Pro® fog nozzles comply with all aspects of U.S. Forest Service specifications. Twist shutoff fog tips are machined from high strength 6061 T-6 aluminum bar stock and have a hard anodized finish. 1-1/2" tip features dual gallonage with 20 GPM on the low setting in straight through narrow fog and in the high range from straight stream through wide angle fog. Ideal for "mop up" or to conserve water in the low range.




FP6095T (Shown)



### REGULARLY FURNISHED

- Combination fog and straight stream
- Lightweight/strong aluminum
- Hard anodized finish - red or gray


MODEL	INLET In (mm)	WEIGHT Lbs (kg)	GPM (lpm)
FP6095T	1-1/2" (38)	1-1/4 (0.6)	20-60 (76-227)
FP6095TB	1-1/2" (38)	1-1/4 (0.6)	20-95 (76-360)



FP6095T



FP6095TB



**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacture's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superceded data. Please visit [potterroemer.com](http://potterroemer.com) for most current specifications

**FT-FP6095T**

Revised: 09/05/18

**MEMBERSHIP**



FIRE EQUIPMENT  
MANUFACTURERS'  
ASSOCIATION

**ONFSA**  
NATIONAL IRRE SPRINKLER ASSOCIATION, INC.



**CASPE**  
American Society of  
Plumbing Engineers



**POTTER ROEMER/FIRE PRO**

Headquarters:  
P.O. Box 3527  
City of Industry, CA  
91744 U.S.A.  
Los Angeles Area  
800-366-3473  
626-855-4890

Also in:  
New York (800) 526-4592  
Chicago (800) 547-3473  
Atlanta (800) 762-0542  
Miami (866) 961-3473  
Dallas (866) 644-3473

[www.potterroemer.com](http://www.potterroemer.com)