

CONSTANT GALLONAGE NOZZLES

FP10835/-BC

SPECIFICATIONS

Potter Roemer/ Fire Pro® constant gallonage monitor nozzles are combination pattern, master stream nozzles with fixed constant flow. The flow rate is factory preset to customer specifications. Nozzles are adjustable from straight stream to a dense fog pattern.



REGULARLY FURNISHED

- Combination fog and straight stream
- Lightweight/strong alloy or brass construction
- Fixed teeth

MODEL	INLET In (mm)	LENGTH In (mm)	WEIGHT Lbs (kg)	GPM (lpm)
FP10835	2-1/2" (65)	7" (178)	4.8 (2.2)	750, 1000 (2839, 3785)
FP10835-BC	2-1/2" (65)	7" (178)	12.5 (5.7)	750, 1000 (2839, 3785)

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacture's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superceded data. Please visit potterroemer.com for most current specifications

MS-FP10835

Revised: 09/05/18

MEMBERSHIP



FIRE EQUIPMENT
MANUFACTURERS'
ASSOCIATION



CASPE
American Society of
Plumbing Engineers

ONFSA
NATIONAL FIRE SPRINKLER ASSOCIATION, INC.



POTTER ROEMER/FIRE PRO

Headquarters:
P.O. Box 3527
City of Industry, CA
91744 U.S.A.
Los Angeles Area
800-366-3473
626-855-4890

Also in:
New York (800) 526-4592
Chicago (800) 547-3473
Atlanta (800) 762-0542
Miami (866) 961-3473
Dallas (866) 644-3473

www.potterroemer.com